

## VAFX Type vibration Eliminator



### Product Description

- VAFX Type vibration Eliminator is designed to be assembled in refrigeration or air conditioning system to lower the vibration from compressors.


### Features

- SUS316L corrugated pipe supports with high corrosion resistance vibration eliminator stronger and more safety.
- Trinity Argon Arc welding of wire sleeve, pipe connector and clamping ring makes the perfect vibration resistance and good compensation for the heat displacement.

### Technical Parameters

Applicable Refrigerants	HCF/HCFC
Applicable Medium Temp	-40°C~+150°C
MAX Working Pressure	See Model Selection table
Maximum Proof Pressure	1.5 time of the M.W.P.

### Configuration



1.Copper bush; 2.Pipe Connector; 3.Clamping Ring.; 4.Corrugated Pipe.; 5.Wire Sleeveing

### Model Selection

Type	Size	Outline Dimension (mm)			Max.Working Pressure (MPa)	Min.Bending Radius (mm)	
		A	L	D		Static(R)	Dynamic(Rd)
VAFX-038-10	3/8	16	210	9.70 <sup>±0.15</sup>	4.5	80	180
VAFX-012-12	1/2	18	230	12.80 <sup>±0.2</sup>		95	215
VAFX-058-16	5/8	20	250	16.10 <sup>±0.2</sup>		120	270
VAFX-034-19	3/4	22	260	19.10 <sup>±0.2</sup>		145	325
VAFX-078-22	7/8	26	300	22.30 <sup>±0.2</sup>		160	360
VAFX-100-25	1	32	330	25.60 <sup>±0.2</sup>	4.2	175	400
VAFX-118-28	1-1/8	30	330	28.70 <sup>±0.2</sup>		175	400
VAFX-114-32	1-1/4	50	400	32.10 <sup>±0.2</sup>		225	510
VAFX-138-35	1-3/8	35	400	35.20 <sup>±0.2</sup>		225	510
VAFX-158-42	1-5/8	42	400	41.50 <sup>±0.30</sup>		3.0	280